

METALCORTEN PROTECTOR

Antirust protection for Corten Steel

▪ CHARACTERISTICS

Metalcorten protector is an antioxidant oil-based protector that slows down the process of rust on ferrous surfaces such as corten steel. The application of the protector confers a protected natural finish avoiding stains and preserving the original surface during long term with easy maintenance. Suitable for use indoors or outdoors on Vertical or horizontal surfaces: Doors, fences, pergolas, furniture, facades, stairs, carpentry, sculptures, ornaments and all kinds of elements architectural and decorative.

▪ SURFACE PREPARATION

Surface must be clean, dry and free of calamine. The rust must be on the surface and free of dust and other contaminants. It is recommended to wash the surface with plenty of water under pressure or with brushes. If the surface has grease, it must be degreased. With suitable detergent or solvent. Let dry and proceed to protection

▪ APPLICATION

The application of metalcorten protector is recommended to be done with a brush, roller or pistol. Apply a first coat on the surface, saturating evenly the areas to be treated. On surfaces verticals start by applying the product below upward to avoid drips. Let dry 6 hours and repeat the application again.

▪ SURFACE PROTECTION

Lightly sand the surface to remove the layers that are poorly adhered and wash with water under pressure or nylon brushes. Let it dry. Apply 1 or 2 coats of METALCORTEN PROTECTOR as requires the surface to renew the protection and thus avoid subsequent deterioration of the surface when it is exposed to humidity and weather.

▪ TECHNICAL DATA

PERFORMANCE	12-14 m ² /L
INTERVAL BETWEEN LAYERS	24h. Drying time: 30 minutes
APPLICATION TEMPERATURE	5°-35°C
MATERIAL CLEANANCE	White Spirit
PACKAGING	1L AND 5L